

Sun Flex Caulking *Elastomeric Joint Sealant*

Product Description and Uses

Sun Flex Caulking is a heavy bodied emulsion type, gun grade elastomeric, high build waterproof sealant. **Sun Flex Caulking** has outstanding elongation properties which allows it to contract and expand with substrates, thereby maintaining a constant seal. An ideal patching material that stays flexible to permanently stop leaks and seal mildew. Adheres to a wide range of surfaces:

- Plywood and Concrete
- Shingles, wood, or asphalt
- Built up Roofing
- Mineral Roll Roofing
- Sheet Metal
- Stucco and tile
- Drywall
- Plastic

Advantages

- ✓ Complete weather-proofing. Withstands wind, driven rain, salt spray, and ponding water.
- ✓ Tenacious adhesion – bonds to almost anything.
- ✓ Great for patching hairline cracks and filling expansion joints.
- ✓ Economical – less material is needed, saving money in material
- ✓ Easy to apply with caulking gun, brush, or broad knife.
- ✓ Water based – environmentally friendly.
- ✓ Resistant to UV degradation.
- ✓ Seals windows and door frames.
- ✓ Low maintenance, easy to repair.

Packaging and Mixing

Sun Flex Caulking is packaged ready to go out of the pail or tube, do not dilute. Also, **Sun Flex Caulking** exhibits a white color, which makes it easier to see when painting and repairing. This single component material is available in 10 oz. tubes, 1 gal. pails and 5 gal. pails.

Coverage

Rates per 40 sq ft at 1/16” thickness:
Approx. 1 gallon.
*Rates will vary depending upon type, porosity, and condition of surface.

Surface Preparation and Installation

All surfaces to be treated need to be completely dry and free of all dirt, oil, or any other contaminants that would impair the adhesion of **Sun Flex Caulking**. Allow for shrinkage. Apply 2 coats to cracks over ¼”, allowing 3-4 hrs. between coats. Feather the edges of all repairs to hide area.

Limitations

Do not apply in below 40 degrees F or in high humidity conditions. Apply **Sun Flex Caulking** when there is no threat of rain, dew or frost. Refer to MSDS sheets for additional health and safety precautions.